



Declaration of Performance

Declaration Number

TEC37CPR2013
+A1:2016

TTSCTPE 200mm–250mm

TecTies Ltd hereby declares that Plain End Clasp Ties TTSCPTPE 200mm–250mm are in conformity with the provisions of:

ZA Annex of EN 845–1 : 2013+A1:2016

Intended Use : Asymmetrical Slip Ties for restraining masonry to a vertical structure whilst allowing in plane movement.

Notified Body: Lucideon Limited
Queens Road
Penkhull
Stoke on Trent ST4 7LQ
Tel. +44 (0)1782 764428

Notified Body Number: 1289

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3**

Essential Characteristics

Compression Load Capacity:	1290N
Tensile Load Capacity: (central hole)	8900N
Displacement at 1/3 Load—Compression	0.56mm
Displacement at 1/3 Load — Tensile	1.13mm
Water Shedding Capability:	Resistant
Durability:	Material Reference 3: Austenitic Stainless Steel Strip Grade 304 18/8 comp. to BS EN 10088/1
Embedment Depth:	62.5mm
Minimum Mortar Designation:	(iv)
Minimum Mortar Joint Width:	10
Recommended Spacing:	As required

Manufactured by:



TecTies Limited
Unit 4
Hurstfield Industrial Estate
Hague Bar
New Mills
High Peak SK22 3AT
United Kingdom
Tel. +44 (0) 1663 749361
Fax: +44 (0) 1663 747897
Web: www.tecties.co.uk

Signed for and on behalf of the manufacturer by:

Bob Wood, Managing Director, on 18th April 2018