



Declaration of Performance

TTSFCVS 275mm and 300mm

Declaration Number

TEC45CPR2013+
A1:2016

Manufactured by:

Tec Ties Limited
Unit 4
Hurstfield Industrial Estate
Hague Bar
New Mills
High Peak SK22 3AT
United Kingdom
Tel. +44 (0) 1663 749361
Fax. +44 (0) 1663 747897
Web : www.tecties.co.uk

TecTies Ltd hereby declares that Safety End Frame Cramps TTSFCVS 275mm and 300mm are in conformity with the provisions of:

ZA Annex of EN845-1 :2013+A1:2016

Intended Use : Asymmetrical Shear Tie with slot in the upstand and a v drip for connecting a new masonry leaf to an existing structure.
Suitable for cavities of 212.5mm to 237.5mm

Notified Body : Lucideon Limited
Queens Road
Penkhull
Stoke on Trent ST4 7LQ
Tel. +44 (0)1782 764428

Notified Body Number : 1289

The system of assessment and verification of constancy of performance for this construction product conforms to System 3

Essential Characteristics

Compression Load Capacity :	1380N
Tensile Load Capacity - top of slot	530N
Displacement at 1/3 Load - Compression	0.36mm
Displacement at 1/3 Load - Tensile	1.07mm
Water Shedding Capability	Resistant
Durability : Material Reference 3 : Austenitic Stainless Steel Strip Grade 304 18/8 Composition to BS EN 10088/1	
Embedment Depth :	62.5mm
Minimum Mortar Designation : (iv)	
Minimum Mortar Joint Width :	10mm
Recommended Spacing :	As required

Signed for and on behalf of the manufacturer by :

Bob Wood, Managing Director, on 18th April 2018
New Mills