



Declaration of Performance

Declaration Number

TEC38CPR2013
+A1:2016

TTSPB 100mm–250mm

TecTies Ltd hereby declares that Plain End Frame Cramps TTSPB 100mm–250mm are in conformity with the provisions of:

ZA Annex of EN 845–1 : 2013+A1:2016

Intended Use : Asymmetrical Slip Ties for connecting masonry to a vertical structure whilst allowing in plane movement.

Notified Body: Lucideon Limited
Queens Road
Penkhull
Stoke on Trent ST4 7LQ
Tel. +44 (0)1782 764428

Notified Body Number: 1289

The system of assessment and verification of constancy of performance for this construction product conforms to System 3

Essential Characteristics

Tensile Load Capacity—top hole	480N
Displacement at 1/3 Load—Tensile	1.01mm
Water Shedding Capability:	Resistant
Durability: Material Reference 3: Austenitic Stainless Steel	Strip Grade 304 18/8 comp. to BS EN 10088/1
Embedment Depth:	62.5mm
Minimum Mortar Designation:	(iv)
Minimum Mortar Joint Width:	10
Recommended Spacing:	As required

Manufactured by:



TecTies Limited
Unit 4
Hurstfield Industrial Estate
Hague Bar
New Mills
High Peak SK22 3AT
United Kingdom
Tel. +44 (0) 1663 749361
Fax: +44 (0) 1663 747897
Web: www.tecties.co.uk

Signed for and on behalf of the manufacturer by:

Bob Wood, Managing Director, on 18th April 2018