



Declaration of Performance

TTSSPE 150mm - 250mm

Declaration Number

TEC28CPR2013+
A1:2016

Manufactured by:

Tec Ties Limited
Unit 4
Hurstfield Industrial Estate
Hague Bar
New Mills
High Peak SK22 3AT
United Kingdom
Tel. +44 (0) 1663 749361
Fax. +44 (0) 1663 747897
Web : www.tecties.co.uk

TecTies Ltd hereby declares that Safety Plain End Movement Ties TTSSPE 150mm - 250mm are in conformity with the provisions of:

ZA Annex of EN845-1 :2013+A1:2016

Intended Use : Asymmetrical Slip Ties for connecting two leaves of masonry whilst allowing in plane movement.

Notified Body : Lucideon Limited
Queens Road
Penkhull
Stoke on Trent ST4 7LQ
Tel. +44 (0)1782 764428

Notified Body Number : 1289

The system of assessment and verification of constancy of performance for this construction product conforms to System 3

Essential Characteristics

Shear Load Capacity :	2610N
Tensile Load Capacity	1950N
Displacement at 1/3 Load - Tensile	0.65mm
Water Shedding Capability	Resistant
Durability : Material Reference 3 : Austenitic Stainless Steel	
	Strip Grade 304 18/8 Composition to BS EN 10088/1
Embedment Depth :	62.5mm
Minimum Mortar Designation : (iv)	
Minimum Mortar Joint Width :	10mm
Recommended Spacing :	As required

Signed for and on behalf of the manufacturer by :

Bob Wood, Managing Director, on 18th April 2018