

DECLARATION NUMBER
TEC28CPR2013 +A1:2016

TTSSPE 150MM-250MM

TecTies Ltd hereby declares that Safety Plain End Movement Ties TTSSPE 150mm - 250mm are in conformity with the provisions of **ZA Annex of EN 845—1 : 2013+A1:2016**

Intended Use

Asymmetrical Slip Ties for connecting two leaves of masonry whilst allowing in plane movement

Notified Body

Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ **Tel.** +44 (0)1782 764428

Notified Body Number 1289

Underwritten by TZUS – Prague

Notified Body Number 1020

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3**

Essential Characteristics

| | |
|------------------------------------|---------------------------------|
| Shear Load Capacity | 2610N |
| Tensile Load Capacity | 1950N |
| Displacement at 1/3 Load - Tensile | 0.65mm |
| Water Shedding Capability | Resistant |
| Durability - Material Reference 3 | Austenitic Stainless Steel |
| Durability - Wire Grade | 304 18/8 comp. to BS EN 10088/1 |
| Embedment Depth | 62.5mm |
| Minimum Mortar Designation | (iv) |
| Minimum Mortar Joint Width | 10mm |
| Recommended Spacing | As required |





Signed for and on behalf of the manufacturer by:



Bob Wood, Tecties Managing Director, on 14th September 2023



visit **www.tecties.co.uk** for more information or call **01663 749361**

 Tecties, Hague Bar Works, Hague Bar, New Mills SK22 3AT
 T: 01663 749361  F: 01663 747897  E: sales@tecties.co.uk