

DECLARATION OF PERFORMANCE

DECLARATION NUMBER TEC38CPR2013 +A1:2016

TTSPB 100MM-250MM

TecTies Ltd hereby declares that Plain End Frame Cramps TTSPB 100mm-250mm are in conformity with the provisions of ZA Annex of EN 845—1:2013+A1:2016

Intended Use

Asymmetrical Slip Ties for connecting masonry to a vertical structure whilst allowing in plane movement.

Notified Body Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ Tel. +44 (0)1782 764428

Notified Body Number 1289 Underwritten by TZUS – Prague

Notified Body Number 1020

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3**

Essential Characteristics

Tensile Load Capacity - top hole	480N
Displacement at 1/3 Load - Tensile	1.01mm
Water Shedding Capability	Resistant
Durability - Material Reference 3	Austenitic Stainless Steel
Durability - Wire Grade	304 18/8 comp. to BS EN 10088/1
Embedment Depth	62.5mm
Minimum Mortar Designation	(iv)
Minimum Mortar Joint Width	10mm
Recommended Spacing	As required

Signed for and on behalf of the manufacturer by:



Bob Wood, Tecties Managing Director, on 14th September 2023





visit **www.tecties.co.uk** for more information or call **01663 749361**

Tecties, Hague Bar Works, Hague Bar, New Mills SK22 3AT
T: 01663 749361
F: 01663 747897
E: sales@tecties.co.uk