

# DECLARATION OF **PERFORMANCE**

DECLARATION NUMBER
TEC11CPR2013 +A1:2016

## **TT1S** 225-350MM

TecTies Ltd hereby declares that the Type 1S are in conformity with the provisions of ZA Annex of EN 845—1: 2013+A1:2016

#### Intended Use

Symmetrical Wall Tie Type 1 /Type B designed to connect two leaves of a cavity wall in masonry construction

#### Suitable for

76—225mm cavities

#### **Notified Body**

Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ **Tel.** +44 (0)1782 764428

Notified Body Number 1289

**Underwritten by TZUS - Prague** 

**Notified Body Number 1020** 

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3** 

### **Essential Characteristics**

	Maximum Declared Mean
Compressive Load Capacity	3239N
Tensile Load Capacity	2840N
Displacement at 1/3 Load - Compression	0.31mm
Displacement at 1/3 Load - Tensile	0.42mm
Water Shedding Capability	Resistant
Durability - Material Reference 3	Austenitic Stainless Steel
Durability - Steel Grade	304 18/8 comp. to BS EN 10088/1
Embedment Depth	62.5mm
Minimum Mortar Designation	(iv)
Minimum Mortar Joint Width	10mm
Recommended Spacing	PD 6697:2010 Clause 6.2.2.2

Signed for and on behalf of the manufacturer by:



Bob Wood, Tecties Managing Director, on 8th November 2023





visit www.tecties.co.uk for more information or call 01663 749361

Tecties, Hague Bar Works, Hague Bar, New Mills SK22 3AT

T: 01663 749361 F: 01663 747897 E: sales@tecties.co.uk