

DECLARATION OF PERFORMANCE

DECLARATION NUMBER
TEC41CPR2013 +A1:2016

TT3 300MM

TecTies Ltd hereby declares that the Type 3 Basic Ties TT3 300mm are in conformity with the provisions of ZA Annex of EN 845—1: 2013+A1:2016

Intended Use

Symmetrical Wall Tie Type 3 /Type B designed to connect two leaves of a cavity wall in masonry construction

Suitable for

126—150mm cavities

Notified Body

Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ **Tel.** +44 (0)1782 764428

Notified Body Number 1289

Underwritten by TZUS - Prague

Notified Body Number 1020

The system of assessment and verification of constancy of performance for this construction product conforms to **System 3**

Essential Characteristics

Compressive Load Capacity	1020N
Tensile Load Capacity	2540N
Displacement at 1/3 Load - Compression	0.14mm
Displacement at 1/3 Load - Tensile	0.34mm
Water Shedding Capability	Resistant
Durability - Material Reference 3	Austenitic Stainless Steel
Durability - Wire Grade	304 18/8 comp. to BS EN 10088/1
Embedment Depth	62.5mm
Minimum Mortar Designation	(iv)
Minimum Mortar Joint Width	10mm
Recommended Spacing	PD 6697:2010 Clause 6.2.2.2

Signed for and on behalf of the manufacturer by:









visit www.tecties.co.uk for more information or call 01663 749361